

### Perimeter Pro (PP) Series

Powered by 16 years of manufacturing experience and robust supply chain resources, EZ LED Visual is dedicated to providing solid and stable LED video display products that enable our clients' designs to shine and amaze their audience. Whether it's information visualization, immersive experiences, mission-critical applications, or interactive display solutions, EZ LED Visual is ready to help you make it happen.

#### **Product Features**


- Product Features
- Pixel pitch: 6.25mm, 8.33mm, 10mm
- Superior image quality powered by Dynamic Pro Technology featuring high brightness, high refresh, and high grayscale
- All-weather IP65 rating allowing for stable operation in rainy and dusty environment
- Light-weight design
- Player protection design:
  - EVA protective cover on the top offering rubber-like softness and flexibility
  - Soft module mask for higher impact resistance
- Adjustable floor stand for different flexible angles
- Wide view angle for higher visibility and exposure
- Movable wheels for open section design (optional)
- Power and data back available (optional)
- Custom high-brightness (≥8000 nits) available (optional)








### **Product Overview**





#### Soft module mask

Offering an extra layer of protective buffer when players hit the LED wall Improving impact resistance



#### **EVA** protective cover

Protecting players from hitting sharp edges or corners



# Front and rear maintenance

Front and rear serviceability to meet different needs depending on site conditions







45 KG/99 LBS



IP65 rated



- Elegant structure
- Seamless splicing
- Perfect flatness

## **Dynamic Pro Technology**

### High brightness



High brightness



Low brightness

#### High refresh



High refresh




Low refresh


#### High grayscale



High grayscale



Low grayscale



### **Adjustable Floor Stand**



LED panel angel can be adjusted to 90°, 95°, 100°, 105°, 110° and 115°



Foldable floor stand




### Power & Data Back Up

available for uninterrupted operation in live sports events

## **Applications** (Sports stadium)







## **Technical Specifications**

EZ LED Perimeter Pro (PP) Series

Product Model	PP 6.25mm	PP 8.33mm	PP 10mm
Panel Size (W*H)	1600x900mm / 63'x 35.4'		
Brightness	Standard: 6000 nits		
	Custom: ≥8000 nits		
Refresh Rate	3840 HZ		
Grayscale	14-16 bit		
Contrast Ratio	5000:1		
View Angle	160° Horizontal/120° Vertical		
panel Weight	45 KG/ 99 LBS		
Per Panel Resolution	256*144	192*108	160*90
Per Panel Power Consumption (max)	1,150W		
Per Panel Power Consumption (typical)	360W		
Installation Access	Front Install/ Rear Install		
Service Access	Front Service/ Rear Service		
Panel Material	Aluminum		
Brightness Uniformity	>97.5%		
Color Uniformity	>97.5%		
Color Gamut	100% NTSC		
Color Temperature	3,000 -10,000 K		
Service Life	100,000 hours		
Working Voltage	100V-240V auto-switching		
Operating Temperature	-20° C -50° C/ -4° F -122° F		

All rights reserved by EZ LED Visual Co.,Ltd.